



Description

VT200 is a cutting-edge digital touchscreen weighing indicator. With the combination of simplified user interface and high-powered built-in functions, the VT200 can meet various requirements for complex industrial processes.

General Features

- Innovative digital touchsreen weighing indicator
- New and advanced built-in functions
- · User-friendly interface with touchscreen display
- Reliable connection with up to 16 digital loadcells
- Trouble-free operation thanks to advanced self-diagnostics built-in function
- Flexible communications with multiple connectivity protocols: RS232, RS485, Modbus - RTU...
- Dual power supply with AC 220V and external DC 12V rechargeable battery

Technical Spo	ecifications
Гуре	Digital touchscreen weighing indicator
Display	7 inch 800*480TFT screen
Keyboard	Resistive touch screen
Repeatability	±0.01% F.S.
Excitation Voltage	DC 12~14.8V
Decimal Points	Configurable
Calibration	Multi-point calibration
Serial communication	Transmission mode RS232 and RS485
nterface	Baud rate: 2400/4800/9600/19200/38400/115200bps
Printing interface	Standard parallel printing interface, such as EPSON LQ-300K + II, EPSON LQ-300K, EPSON LQ-680K, EPSON LQ-730K, EPSON LQ-1600K (+), KX-P1131, KX-P1121, DS-300etc printers.
Data storage	Can store up to 1000 groups of vehicle numbers and tare weight, 4000 groups of latest weighing records, 300 groups latest unfinished weighing records, 6 groups of over load records.
Operating environment	Operation temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Storage temperature $-25^{\circ}\text{C} \sim 55^{\circ}\text{C}$ Relative humidity $\leq 85\%\text{RH}$
Power Input	AC 110~220V, 50~60Hz DC 12V
Dimension	330(L) x 207(W) x 185(H) (mm)
Shipping Weight	6.8 kg (15 lbs)